



Integrated Amplifiers at a Glance

	240i	250i	340i	600i	700i
Configuration	2-channel		2-channel	2-channel	Dual-Mono
Power Output - 8Ω	50 W/ch.		50 W/ch.	100 W/ch.	125 W/ch.
Power Output - 4Ω	75 W/ch.		100 W/ch.	200 W/ch.	250 W/ch.
Single-ended inputs (RCA)	2		5	4	5
Balanced inputs (XLR)	n/a		n/a	1	1
Front panel input	1/8" mini-jack		1/8" mini-jack	1/8" mini-jack	No
Headphone output	Yes		Yes	Yes	No
Variable level output	Yes		Yes	Yes	Yes
Fixed level output	No		No	Yes	Yes
Tape Monitor Loop	No		No	No	Yes
DAC / Digital input	Yes		No	optional	No
Phono Stage	Yes – MM only		No	optional	No
S/N Ratio @ Full Power	100dB		101dB	110dB	120dB
THD @ Full Power	< 0.02%		< 0.02%	< 0.05%	< 0.04%
12V Trigger Output	No		No	Yes	Yes
RS-232 Port	Yes		Yes	Yes	Yes
Infra-Red (IR) Input	Yes		Yes	Yes	Yes
SimLink	Yes		Yes	Yes	Yes
Home-Theater Gain Bypass	Yes		No	Yes	Yes
Remote Control	CRM-3		CRM-3	CRM-3	FRM-3
Weight (lbs.)	24		22	28	48
Dimensions (W" x H" x D")	16.9 x 3.5 x 14.8		16.9 x 3.5 x 14.8	16.9 x 3.5 x 14.8	18.8 x 4.0 x 18.1
					18.8 x 5.4 x 18.1