

# Tableau comparatif - Convertisseurs N/A (DAC)

	ACE	260D <sup>1</sup>	280D	340i DPX <sup>1</sup>	390	650D	780D v2	230HAD	430HA <sup>1</sup>
Alimentation externe	○	○	○	○	○	820S optionnel	820S optionnel	○	○
Entrée S/PDIF	●	●	●	●	●	●	●	●	●
Entrée AES/EBU	○	○	●	○	●	●	●	○	○
Entrée TosLink	●	●	●	●	●	●	●	●	●
Entrée USB <sup>2</sup>	●	24-bit/192kHz	●	●	●	24-bit/192kHz	●	●	●
Entrée Bluetooth®	●	○	●	○	●	○	●	○	○
Support DSD (par USB)	●	○	●	●	●	○	●	●	●
Sortie asymétrique (RCA)	n/a	●	●	n/a	2 paires <sup>3</sup>	1 paire	●	●	●
Sortie balancée (XLR)	n/a	●	●	n/a	1 paire	●	●	○	○
Sortie digitale - S/PDIF	n/a	●	○	n/a	n/a	●	○	○	○
Sortie digitale - AES/EBU	n/a	●	○	n/a	n/a	●	○	○	○
Port RS-232	●	●	●	●	○	●	●	○	●
Entrée Infra-Rouge (IR)	●	●	●	●	●	●	●	○	●
SimLink™	●	●	●	●	●	●	●	○	●
Module MiND	●	○	Optionnel	○	●	○	●	○	○
Lecture DSD via MiND	●	○	●	○	●	○	●	○	○
Rapport signal/bruit	> 115dB	> 120dB	> 118dB	> 110dB	> 125dB	> 120dB	> 124dB	> 115dB	> 116dB
DHT @ 1kHz, 0dBFS	< 0.001 %	< 0.005 %	< 0.001 %	< 0.001 %	< 0.0004 %	< 0.001 %	<0.0001 %	< 0.001 %	< 0.001 %
Télécommande	CRM-3	CRM-3	CRM-3	CRM-3	CRM-3	FRM-3	FRM-3	CRM-3	CRM-3
Poids (lb)	24	16	16	28	22	35	38	6.2	17
Dimensions (l" x h" x p")	16.9x3.5x14.4	16.9x3.4x13.1	16.9x3.4x13.1	16.9x3.5x14.8	16.9x3.5x13.1	18.8x4.0x16.8	18.8x4.0x16.8	7.0x3.0x11.0	16.9x3.5x13.8

<sup>1</sup> Module DAC optionnel

<sup>2</sup> L'entrée USB input est compatible 32-bit/384kHz sauf si indiqué

<sup>3</sup> 1 paire est une sortie analogique variable optionnelle